

Weekly Check

The check shall be performed at intervals not to exceed 36 hours.

The tasks within the inspection are intended to be carried out on a walk around and assessed from ground level with no external access requirements; appropriate lighting should be used to satisfy the requirements.

ITEM	CHECKED Date / Initial / Stamp
GENERAL	
Record APU Hours & Cycles: APU HRS _____ APU CYC _____ DATE _____	
Interrogate CIDS from FAP for any class 3 faults on cabin lighting – rectify as required.	
Ensure spare bulbs box in flight deck is topped up.	
Ensure spare printer rolls in flight deck contains 3 rolls.	
Upon completion of the weekly check – make an entry in the technical log and record sector page: _____	

FUSELAGE	
MAIN HYDRAULIC POWER - CHECK NITROGEN CHARGING PRESSURE ON HYDRAULIC POWER ACCUMULATORS. REF MPD 291000-06-1	
Lower deck forward cargo compartment Visual check of linings, floor panels, sealing strips, protection plates, centre line cover plates, access doors, decompression panels and pressure equalization valves. Note - planning: crew rest room (underfloor) and/or acts not to be removed if installed REF MPD 255200-01-1	
Lower deck aft cargo compartment Visual check of linings, floor panels, sealing strips, protection plates, centre line cover plates and decompression panels. Note - planning: - crew rest room (underfloor) and/or acts not to be removed if installed REF MPD 255300-01-1	
Lower deck bulk cargo compartment Visual check of linings, floor panels, sealing strips, access door at C 73, decompression panels and pressure equalization valve. REF MPD 255400-01-1	
Check Hydraulic fluid levels and service as required / record qty uplift below: Green:_____ Blue:_____ Yellow:_____	
Clean flight deck windows 1 LH, 2 LH, 3 LH, 1 RH, 2 RH, 3 RH	
Check all cabin illumination lighting operates including: Main cabin lights, reading lights, no smoking & fasten seat belts	
Check cabin emergency lighting functions.	

Weekly Check

The check shall be performed at intervals not to exceed 36 hours.

The tasks within the inspection are intended to be carried out on a walk around and assessed from ground level with no external access requirements; appropriate lighting should be used to satisfy the requirements.

ITEM

CHECKED
Date /
Initial /
Stamp

LANDING GEAR

Main gear and doors - lubrication of MLG and doors.
REF MPD 321000-03-1

Main gear and doors - lubrication of MLG bogie beam pivot pin.
REF MPD 321000-04-1

Record MLG Brake wear length remaining (in MM) with Park Brake applied:

1:	2:	3:	4:
5:	6:	7:	8:

WINGS

Fuel tanks - operate water drain valves to drain accumulated water from centre, inner, outer and wing vent surge tanks.

Note - interval:

- operators are advised to optimise the interval of this task according to their operating environment and experience. This may result in a less or more frequent interval

REF MPD 281100-10-1

Deploy Flaps and Slats – Perform a visual check from the ground for any damage, leakage and installation (missing fasteners).

Weekly Check

The check shall be performed at intervals not to exceed 36 hours.

The tasks within the inspection are intended to be carried out on a walk around and assessed from ground level with no external access requirements; appropriate lighting should be used to satisfy the requirements.

ITEM	CHECKED Date / Initial / Stamp
ENGINES	
Pneumatic starter and valve system - starter oil replenishment. REF MPD 801100-R1-1	
EMPENNAGE	
Check APU oil level and top up as required.	